

Specifications:

Description:

Halius Lysander Smart touch panel with built in gateway provide full control of device from single touch panel. Supports one-key pairing, UI style switching, weather details checking, smart home devices control, smart scenes control, etc. User friendly operations. Trigger scenes with a tap, Even if the Internet is interrupted, device control and device linkage can still work normally in the LAN.

Construction:

- Android OS.
- PoE Power supply.
- Compact size and easy installation.
- Elegant look.
- Custom physical buttons to switch scenes.
- Microphone and speaker integrated
- Application control.
- Voice Control.

Performance:

Input	DC 12V/PoE 48V
Screen	7 Inch
Resolution	1024*600(IPS)
Interface	PoE
CPU	4 core ARM
Radio Frequency	CoSS:433MHz Others: 2.4GHz
Microphone	Yes
Speaker	Yes
Protocol	Coss, Zigbee, Wi-Fi,Bluetooth
Signal range(open feild)	CoSS: 300m Others: 50m
Operating System	Android 11
Color	Grey
Body	PC
Dimension(LxWxH)	249x113x28.6mm
Weight	525gm
Operating Temperature Operating	-5 to 45 degree
Humidity	5-90%
Voice Control	Yes
App Control	Yes

HL-AUTO-I-FED-LYSANDER7-B-G

Images:



Ordering Code:

HL-AUTO-I-FED-LYSANDER7-B-G