

Specifications:

Description:

Halius Theo helps to replace your traditional switch to the smart one and make the devices freely controlled. Combined with the Smart Hub and Smat Application can have infinite control possibilities. With one button you can choose to turn on your television, stereo, air conditioner, space heater, and coffee maker individually or all at once, even across the house.

Construction:

- Dual control, multiple control.
- Voice control support.
- Wireless communication for smart devices.
- Remotely control various smart devices.
- Support Resistive, Capacitive and inductive load.
- 1, 2 & 3 Gang options available.
- Customized 16 million colors panel light.
- Simple and Luxury design.
- Easy Mounting.

Performance:

Input Power	AC 100-240V 50/60Hz
Consumption	<1.5W
Wiring	Live and Neutral
Indicator	16Million colors, brightness adjusted
Maximum Load	500W Resistive, 200W Capacitive/Inductive
Swich	1Gang/2Gang/3Gang
Radio Protocol	CoSS
Signal Distance	200m(Open space)
Color	White / Black / Golden / Grey
Body	ABS + PC
Dimension(LxWxH)	86x86x36.5mm
Control Mode	Dual and Multiple
Operating Temperature	-5 to 45 degree
Operating Humidity	5-90%
Voice Control	Yes
App Control	Yes
Operating Humidity	5-90%
Weight	100g(1G), 110g(2G), 120g(3G)

HL-AUTO-I-SSW-THEO-1G-B/G/W

Images:



Ordering Code:

HL-AUTO-I-SSW-THEO-1G-B/G/W
 HL-AUTO-I-SSW-THEO-2G-B/G/W
 HL-AUTO-I-SSW-THEO-3G-B/G/W