

Specifications:

Description:

Halius Theodore smart switches helps to replace your traditional switch to the smart one and make the devices freely controlled. Combined with the Smart Hub and Smart Application can have infinite control possibilities. With one button you can choose to turn on your television, stereo, air conditioner, space heater, and coffee maker individually or all at once, even across the house. Independent power supply, perfect solution for live only wiring.

Construction:


- Dual control, multiple control.
- Voice control support.
- Wireless communication for smart devices.
- Remotely control various smart devices.
- Support Resistive, Capacitive and inductive load.
- 1, 2 & 3 Gang options available.
- Live only wiring.
- Luxury design.
- Easy Mounting.

Performance:

Input Power	DC 5V-30V Or AC 90-250Vac
Consumption	<1mW
Wiring	Live only / Live + neutral
Dual Control	No wiring
Maximum Load	500W Resistive, 200W Capacitive/Inductive
Swich	1Gang/2Gang/3Gang
Radio Protocol	CoSS
Signal Distance	200m(Open space)
Color	White / Black / Golden / Grey
Body	ABS + PC
Dimension(LxWxH)	86x86x39mm
Control Mode	Dual and Multiple
Operating Temperature	-5 to 45 degree
Operating Humidity	5-90%
Voice Control	Yes
App Control	Yes
Operating Humidity	5-90%
Weight	125g(1G), 135g(2G), 144g(3G), 110g(Dual)
Battery Type/Life	CR17505 / 5yrs

HL-AUTO-I-SSW-THEODORE-XG-B/G/W

Images:



Ordering Code:

HL-AUTO-I-SSW-THEODORE-1G-B/G/W
 HL-AUTO-I-SSW-THEODORE-2G-B/G/W
 HL-AUTO-I-SSW-THEODORE-3G-B/G/W